



Twin 422

TWIN FORESTRY

Steel reinforced, high performance tyre for rough forestry service. The pattern is designed for traction and flotation without damaging the ground.

710/45-26.5 163 A8 T422 SB FS

600/65-34 157 A8 T422 SB FS

710/55-34 161 A8 T422 SB FS

750/65-34 169 A8 T422 SB FS

650/45-22.5 135 A8 T422 FS

650/45-22.5 150 A8 T422 SB FS

600/55-26.5 154 A8 T422 SB FS

710/45-26.5 151 A8 T422 SB FS

650/45-22.5 135 A8 T422 FS

650/45-22.5 150 A8 T422 SB FS

600/55-26.5 154 A8 T422 SB FS

710/45-26.5 151 A8 T422 SB FS

600/50-22.5 143 A8 T428 FS

600/50-22.5 149 A8 T428 SB FS

710/40-22.5 145 A8 T428 FS

710/40-22.5 151 A8 T428 SB FS

600/55-26.5 160 A8 T428 SB FS

650/60-26.5 161 A8 T428 SB FS

710/45-26.5 151 A8 T428 SB FS

710/45-26.5 163 A8 T428 SB FS

750/50-26.5 170 A8 T428 SB FS

620/55-30.5 158 A8 T428 SB FS

750/45-30.5 169 A8 T428 SB FS



Twin 428



Twin 423

TWIN AMPT

(Agricultural Multi Purpose Tyre)

Low ground pressure tyres for all round service in the field and on the road. Designed for speeds up to 65km/h.

850/40B - 26.5 TL 173 D T423MK2

850/45B - 30.5 TL 176 D

620/50B - 22.5 TL 160 D T423

850/40B - 22.5 TL 161 D T423

850/45B - 26.5 TL 170 D T423MK2

Trelleborg Wheel Systems S.p.A.

Registered office and head office: Via Nazionale Tiburtina, 143 - 00010 Villa Adriana (Roma)

Trade office: Resolution Road, Flagstaff 42 Ashby de la Zouch, Leicestershire, LE65 1DW

Tel. +44 (0) 845 6011082 - Fax +44 1530



NO ONE IS CLOSER TO THE EARTH



NO ONE IS CLOSER TO THE EARTH

**TRELLEBORG
WHEEL SYSTEMS
AGRICULTURAL TYRES**

**OUR WIDE RANGE:
JUST ANOTHER STRENGTH**

TWIN IMPLEMENT

Low ground pressure tyre, designed for mainly field service, available in a wide range of tread patterns.



TWIN 404

A gentle pattern for sensitive ground conditions with rounded shoulders and a large contact surface.

New

400/60-15.5 TL 145 A8 T404	750/45-22.5 TL 165 A8 T404
400/55-17.5 131 A8 T404	400/60-26.5 147 A8 T404
400/55-22.5 147 A8 T404	600/55-26.5 TL 166 A8 T404
500/45-22.5 TL 146 A8 T404	710/45-26.5 TL 169 A8 T404
560/45-22.5 TL 154 A8 T404	(replaces 700/50-26.5)
(replaces 550/45-22.5)	800/40-26.5 TL 172 A8 T404
500/60-22.5 TL 155 A8 T404	650/65-30.5 TL 173 A8 T404
560/60-22.5 TL 158 A8 T404	710/50-30.5 TL 175 A8 T404
(replaces 550/60-22.5)	(replaces 700/50-30.5)
560/60-22.5 TL 167 A8 T404	750/60-30.5 TL 178 A8 T404
(replaces 550/60-22.5)	800/45-30.5 TL 178 A8 T404
600/50-22.5 TL 156 A8 T404	850/50-30.5 TL 179 A8 T404
650/50-22.5 TL 160 A8 T404	
710/40-22.5 TL 158 A8 T404	
(replaces 700/40-22.5)	



TWIN 421 TWIN 423

Soft traction pattern with an open tread for good traction and self cleaning. Its rounded shoulder provides smooth ground contact.

New

280/60-15.5 TL 115 A8 T421	600/60-30.5 TL 171 A8 T421
500/60-22.5 TL 155 A8 T421	650/65-30.5 TL 173 A8 T421
500/60-26.5 TL 159 A8 T421	750/60-30.5 TL 178 A8 T421
600/55-26.5 TL 166 A8 T421	

600/50-22.5 TL 156 A8 T423
710/45-26.5 TL 169 A8 T423 _{MIC}
(replaces 700/50-26.5)
800/40-26.5 TL 172 A8 T423 _{MIC}
710/50-30.5 TL 175 A8 T423
(replaces 700/50-30.5)
800/45-30.5 TL 178 A8 T423



New

Twin 423



TWIN 478

Long grooved pattern with low rolling resistance on road service. Rounded shoulders give smooth contact towards the ground.

New

280/60-15.5 128 A8 T478	400/60-15.5 TL 145A8 T478
-------------------------	---------------------------



TWIN RADIAL

Highly practical in the field, it delivers excellent performance on the road. Ideal on all kind of soils.

560/60 R 22.5 TL 161 D	680/55 R 26.5 TL 165 D
580/65 R 22.5 TL 159 D	



TM 2000

For combines and harvesting machines, it offers excellent loading and traction properties combined with excellent lateral stability and resistance to wear.

620/75 R 26 TL 166 A8	23.1 R 26
800/65 R 32 TL 172 A8	30.5 LR 32
800/65 R 32 TL 178 A8	30.5 LR 32
650/75 R 32 TL 172 A8	24.5 R 32
900/60 R 32 TL 176 A8*	

Correspondence

(* Design Data)



TWIN TRACTOR

Traction pattern with deep effective lugs in three different angles for maximum traction and excellent self cleaning.

400/55-17.5 TL 125 A8 T414	710/55-34 TL 155 A8 T414
360/60-24 TL 122 A8 T421	800/50-34 TL 151 A8 T414
400/60-26.5 TL 116 A8 T414	600/60-38 TL 156 A8 T414
500/60-26.5 TL 141 A8 T414	650/60-38 TL 161 A8 T414
600/55-26.5 TL 148 A8 T414	710/65-38 TL 161 A8 T414
600/55-30.5 TL 150 A8 T414	750/65-38 TL 158 A8 T414
600/60-30.5 TL 153 A8 T414	750/65-38 TL 171 A8 T414
750/45-30.5 TL 143 A8 T414	850/50-38 TL 163 A8 T414
750/50-30.5 TL 159 A8 T414	850/60-38 TL 162 A8 T414
800/55-30.5 TL 172 A8 T414	850/60-38 TL 175 A8 T414
900/60-32 TL 176 A8 T414	850/55-42 TL 161 A8 T414



IMPLEMENT STANDARD

General-purpose tyre for implements and trailers. Available in a wide range of sizes and patterns.

New

200/95-12 TL 101 A8 AF 302	300/80-15.3 TL 141 A8 AW 305
(replaces 7.00-12)	(replaces 11.5/80-15.3)
260/90-13 TL 121 A8 AF 302	320/80-15.3 TL 145 A8 AW 305
(replaces 9.00-13)	(replaces 12.5/80-15.3)
180/90-16 TL 100 A8 AF 302	260/70-16 TL 134 A8 AW 305
(replaces 6.00-16)	(replaces 10.5/65-16)
190/90-16 TL 108 A8 AF 302	340/55-16 TL 140 A8 AW 305
(replaces 6.50-16)	(replaces 13.0/55-16)
200/90-16 TL 111 A8 AF 302	360/70-16 TL 137 A8 AW 305
(replaces 7.00-16)	(replaces 13.0/75-16)
210/95-16 TL 120 A8 AF 302	360/65-16 TL 148 A8 AW 305
(replaces 7.50-16)	(replaces 14.0/65-16)
260/70-15.3 TL 116 A8 AW 305	380/55-17 138 A8 AW 305
(replaces 10.0/75-15.3)	480/45-17 146 A8 AW 305
260/70-15.3 TL 126 A8 AW 305	520/50-17 159 A8 Rib Trailer 306
(replaces 10.0/75-15.3)	10.0/80-12 TL 8 PR AW 305
260/70-15.3 TL 131 A8 AW 305	10.0/80-12 TL 10 PR AW 305
(replaces 10.0/75-15.3)	10.0/75-15.3 8 PR T 307
300/80-15.3 TL 132 A8 AW 305	11.5/80-15.3 8 PR T 307
(replaces 11.5/80-15.3)	